



- Equipped with reliable Chinese engine.
- Domestic unique design of vacuum device for hydraulic oil tank, which could prevent oil leaking, assure oil clean, more convenient for repair and maintenance.
- More efficient, total three item time for working device is 11.8s for 955&ZLM40E, 9.2s for ZLM30E.
- Engine hood turning-up design, supply more space for maintenance and repair.
- More optional accessory working implements: Bale Grapppler, Fork, Log Clamp, ROPS Frame, Side-dump Bucket, Snowplow.
- Whole machine has high performance and cost ratio.

Model		ZLM30-5	ZLM40E	955
Overall Dimension ( L×W×H )	mm	6720 × 2350 × 3095	7165 × 2570 × 3360	8100 × 2800 × 3500
Rated load	kg	3000	4000	5000
Rated bucket capacity	m <sup>3</sup>	1.7	2.3	3.0
Max. dump clearance	mm	2820	2815	3050
Min. turning radius	mm	5340	6300	5970
Lifting time of bucket	sec.	≤6.3	6.2	≤6.2
Lowering time of bucket	sec.	≤4.0	3.8	≤3.8
Dumping time	sec.	≤2.0	1.8	≤1.8
Traveling speed	km/h	3 forward and 3 reverse	2 forward and 1 reverse	2 forward and 1 reverse
1st gear forward		7.2	11	12
2nd gear forward		18	36	37
3rd gear forward		34	-	-
1st gear reverse		8.95	15	16
2nd gear reverse		22.6	-	-
3rd gear reverse		42	-	-
<b>Diesel engine</b>				
Model		LR6108G6F	SHANG CHAI 6135K-13b	WD615G.220
Rated output	kW	92	128	162
Rated speed	r/min.	2200	2000	2200
Min. specific fuel consumption	g/kW.h	≤242	≤237.9	≤226
Working Device Hydraulic System pressure	Mpa	14	18	20
Fuel capacity	L	120	200	250